

SO 105 SAFETY DATA SHEET



1 . Identification

Product identifier SO105 SCREEN OPENER
Company information RHINOTECH INC
2955 LONE OAK CIRCLE, UNIT 2
EAGAN, MN 55121 United States
Company phone General Assistance 651-686-5027
Emergency telephone ChemTel, Inc. 800-255-3924, International 813-248-0585

US

Version # 01
Recommended use Lubricant
Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1
Health hazards Skin corrosion/irritation Serious eye damage/eye irritation
Category 2Category 2
Carcinogenicity Category 2
Specific target organ toxicity, single exposure Category 3 respiratory tract irritation
Aspiration hazard Category 1
OSHA defined hazards Not classified.

Label elements



Signal word Danger
Hazard statement Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. Suspected of causing cancer.
Precautionary statement
Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response	If swallowed: Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Environmental hazards	Hazardous to the aquatic environment, acute Category 3 hazard Hazardous to the aquatic environment, Category 3 long-term hazard

Product name: SO105 SCREEN OPENER SDS US Issue date: 09-14-2020 1 / 11

Hazard(s) not otherwise Harmful to aquatic life. Harmful to aquatic life with long lasting effects. classified (HNOC)

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	20 - 40
Solvent Naphtha (Petroleum), Light Aromatic		64742-95-6	20 - 40
1,2,4-Trimethyl Benzene		95-63-6	10 - 20
Cyclohexanone		108-94-1	10 - 20
Propane		74-98-6	2.5 - 10
Xylene		1330-20-7	1 - 2.5
Other components below reportable levels			0.1 - 1

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

treatment needed General information

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. Headache. Dizziness. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special	

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the

as an extinguisher, as this will spread the fire.

5 . Fire-fighting measures

Suitable extinguishing media

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Unsuitable extinguishing media

Specific hazards arising from the chemical

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special protective equipment and precautions for firefighters

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Fire fighting equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. In the event of fire and/or explosion do not breathe fumes.

6. Accidental release measures

Personal precautions, protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of amaged containers or spilled material unless wearing appropriate protective clothing. the SDS. emergency procedures

SO105 SCREEN OPENER

SDS US

Issue date: 09-14-2020

2 / 11

Specific methods

Extremely flammable aerosol

General fire hazards material(s) involved, and take precautions to protect themselves.

Methods and materials for containment and cleaning up

Alcohol resistant foam.

Environmental precautions

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Dry powder. Carbon dioxide (CO2).

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Do not use water jet

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. **Level 3 Aerosol.**

Conditions for safe storage, including any incompatibilities discharge into drains, water courses or onto the ground.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Cyclohexanone (CAS 108-94-1)	PEL	200 mg/m ³
Propane (CAS 74-98-6)	PEL	50 ppm 1800 mg/m ³
Xylene (CAS 1330-20-7)	PEL	1000 ppm 435 mg/m ³ 100 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Butane (CAS 106-97-8)	STEL	1000 ppm
Cyclohexanone (CAS 108-94-1)	STEL	50 ppm
Xylene (CAS 1330-20-7)	TWA	20 ppm
	STEL	150 ppm
	TWA	100 ppm

US. NIOSH: Pocket Guide to Chemical Haz Components

Components	Type	Value
1,2,4-Trimethyl Benzene (CAS 95-63-6)	TWA	125 mg/m ³
Butane (CAS 106-97-8)	TWA	25 ppm 1900 mg/m ³
Cyclohexanone (CAS 108-94-1)	TWA	800 ppm 100 mg/m ³ 25 ppm

Product name: SO105 SCREEN OPENER

SDS US

Issue date: 09-14-2020

3 / 11

**US. NIOSH: Pocket Guide to Chemical Hazards
Components**

Type

Value

1000 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components

Value

Determinant

Specimen

Sampling Time

Cyclohexanone (CAS
108-94-1)

80 mg/l

1,2-Cyclohexan
ediol, with
hydrolysis

Urine

*

* - For sampling details,
please see the source
document.

8 mg/l

Cyclohexanol,
with hydrolysis

Urine

*

Xylene (CAS 1330-20-7)

1.5 g/g

Methylhippuric
acidsCreatinine in
urine

*

Exposure guidelines US - California OELs: Skin designation

Cyclohexanone (CAS 108-94-1)

Can be absorbed through the skin.

US -

Minnesota Haz Subs: Skin designation applies

Cyclohexanone (CAS 108-94-

1) Skin designation applies.

US - Tennessee OELs: Skin designation

Cyclohexanone (CAS 108-94-1)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Cyclohexanone

(CAS 108-94-1) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Cyclohexanone (CAS 108-94-1)

Can be absorbed through the skin.

Appropriate engineering Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates controls should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not

been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product. Individual protection measures, such as personal protective equipment

Eye/face protection **Wear safety glasses with side shields (or goggles).**

Skin protection

Hand protection **Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.**

Other **Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.**

Respiratory protection **If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.**

Thermal hazards **Wear appropriate thermal protective clothing, when necessary.**

General hygiene considerations **Observe any medical surveillance requirements. When using do not smoke. Always observe good**

personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state **Gas.**

Form **Aerosol.**

Color **Not available.**

Odor **Not available.**

Odor threshold **Not applicable**

pH **estimated Not available.**

Melting point/freezing point **Not available.**

Initial boiling point and boiling range

Product name: SO105 SCREEN OPENER

SDS US

Issue date: 09-14-2020 4 / 11 Flash point -156.0 °F (-104.4 °C) Propellant estimated Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower 0.9 % estimated (%)

Flammability limit - upper Not available.

(%)	
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	50 - 65 psig @70F estimated
Vapor density	Not available. Not available.
Relative density	
Solubility(ies)	Not available.
Solubility	Not available.
(water)	
Partition coefficient (n-octanol/water)	875.75 °F (468.75 °C) estimated Not available. Not available.
Auto -ignition temperature	
Decomposition tem perature	Not explosive. Not oxidizing.
Viscosity	0.445 estimated
Other information	
Explosive properties	
Oxidizing properties	
Specific gravity	

10. Stability and reactivity

Reactivity	The product is stable and non -reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions. Hazardous polymerization does not occur.
Possibility of hazardous reactions	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Conditions to avoid	Strong acids. Strong oxidizing agents. Nitrates. Halogens. Fluorine. Chlorine.
Incompatible materials	No hazardous decomposition products are known.
Hazardous decomposition products	

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause irritation to the respiratory system. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. Headache. Dizziness. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
May cause respiratory irritation. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity
respiratory irritation.

May be fatal if swallowed and enters airways. May cause

Product	Species	Test Results
---------	---------	--------------

Acute

Dermal

LD50 Rat 2473 mg/kg

Product name: SO105 SCREEN OPENER

SDS US

Issue date: 09-14-2020

5/11

Product	Species	Test Results
Inhalation		
LC50	Rat	13 mg/l/4h
Oral		
LD50	Rat	

Components	Species	Test Results
------------	---------	--------------

1,2,4-Trimethyl Benzene (CAS 95-63-6)

Acute Dermal

LD50 Rabbit
Rat
> 3160 mg/kg
3440 mg/kg, 24 Hours

Inhalation
VAPOR
LC50 Mouse, Rat
Rat
> 2000 ppm, 12 Hours
10200 mg/m3, 4 Hours
Oral
LD50 Rat
6000 mg/kg

Butane (CAS 106-97-8)

Acute

Inhalation
LC50 Mouse
Rat
1237 mg/l, 120 Minutes
52 %, 120 Minutes
1355 mg/l

Cyclohexanone (CAS 108-94-1)

Acute

Inhalation
LC50 Rat
> 6.2 mg/l, 4 Hours
Oral
LD50 Rat
1620 mg/kg

Propane (CAS 74-98-6)

Acute

Inhalation
LC50 Mouse
Rat
1237 mg/l, 120 Minutes
52 %, 120 Minutes
1355 mg/l
658 mg/l/4h

Solvent Naphtha (Petroleum), Light Aromatic (CAS 64742-95-6)

Acute Dermal

LD50 Rabbit
> 1900 mg/kg, 24 Hours

Inhalation			
LC50	Rat	> 5000 mg/m3, 4 Hours	> 4980 mg/m3
		> 4980 mg/m3, 4 Hours	> 4.96 mg/l, 4 Hours
Oral			
LD50	Rat	> 5000 mg/kg	

Product name: SO105 SCREEN OPENER SDS US Issue date: 01-14-2016 6 / 11

Components	Species	Test Results
------------	---------	--------------

Xylene (CAS 1330-20-7)

Acute

Dermal

LD50	Rabbit	> 5000 ml/kg, 4 Hours	12126 mg/kg, 24 Hours
------	--------	-----------------------	-----------------------

Inhalation

LC50	Rat	5922 ppm, 4 Hours
------	-----	-------------------

Oral

LD50	Mouse	5251 mg/kg
	Rat	3523 mg/kg
		10 ml/kg

* Estimates for product may be based on a additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitization	Not a respiratory sensitizer.
Respiratory sensitization	This product is not expected to cause skin sensitization.
Skin sensitization	No data available to indicate product or any components present at greater than
Germ cell mutagenicity	0.1% are mutagenic or genotoxic.
Carcinogenicity	Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Cyclohexanone (CAS 108-94-1)	3 Not classifiable as to carcinogenicity to humans.	Xylene (CAS 1330-20-7)
	3 Not classifiable as to carcinogenicity to humans.	

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not available.

Reproductive toxicity Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.

Specific target organ toxicity - May cause respiratory irritation.

single exposure Specific target organ

toxicity - Not classified.

repeated exposure Aspiration hazard May be fatal if swallowed and enters airways. Chronic effects Prolonged

inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Product	Species	Test Results
15 OZ SO105 SCREEN OPENER LB 12PK		
Aquatic		
Algae	IC50	Algae 392 mg/L, 72 Hours
Crustacea	EC50	Daphnia 10.8358 mg/L, 48 Hours
Fish LC50	Fish 17.1633 mg/L, 96 Hours	Components Species Test Results

1,2,4-Trimethyl Benzene (CAS 95-63-6)		
Aquatic		
Crustacea	EC50	Daphnia 6.14 mg/L, 48 Hours
Fish	LC50	Fathead minnow (Pimephales promelas) 7.19 - 8.28 mg/l, 96 hours

Product name: SO105 SCREEN OPENER

Issue date: 09-14-2020

SDS US

7 / 11

Components	Species	Test Results
Cyclohexanone (CAS 108-94-1)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 481 - 578 mg/l, 96 hours
Solvent Naphtha (Petroleum), Light Aromatic (CAS 64742-95-6)		
Aquatic		
Crustacea	EC50	Daphnia 6.14 mg/L, 48 Hours
Xylene (CAS 1330-20-7)		
Aquatic		
Fish	LC50	Bluegill (Lepomis macrochirus) 7.711 - 9.591 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Butane	2.89
Cyclohexanone	0.81
Propane	2.36
Xylene	3.12 - 3.2

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Local disposal regulations all applicable regulations.
 Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
 Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
 Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Transport hazard class(es)	2.1
Class	-
Subsidiary risk	2.1
Label(s)	Not applicable. Read safety instructions, SDS and emergency procedures before handling. N82
Packing group	306 None
Special precautions for user	None
Special provisions	None
Packaging exceptions	
Packaging non bulk	UN1950

Product name: SO105 SCREEN OPENER

SDS U

Issue date: 09-14-2020

8 / 11

Packaging bulk	Aerosols, flammable
IATA	2.1
UN number	-
UN proper shipping name	
Transport hazard class(es)	Label(s)
Class	Packing group
Subsidiary risk	Environmental hazards
	ERG Code
Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations. Dispose in accordance with	Special precautions for user
	Other information
	Passenger and cargo aircraft
	Cargo aircraft only
	Packaging Exceptions IMDG
	UN number
	UN proper shipping name Transport hazard class(es)
	Class Subsidiary risk
	Label(s)
	Packing group Environmental hazards
	EmS Marine pollutant
	Special precautions for user
	Packaging Exceptions
	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
	DOT



2.1 Not applicable. No.
10 L Read safety instructions, SDS and emergency procedures before handling.

IATA; IMDG



Allowed with restrictions.

Allowed with restrictions.

LTD QTY

UN1950
AEROSOLS

2.1

-

2.1

Not applicable.

No. F-D,

S -U

Read safety instructions, SDS and emergency procedures before handling. LTD QTY Not applicable.

15 . Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated. CERCLA Hazardous Substance List
(40 CFR 302.4)

Cyclohexanone (CAS 108-94-1) Listed. Xylene (CAS 1330-20-7)
Listed.

SARA 304 Emergency release notification

Not regulated.

Product name: SO105 SCREEN OPENER SDS US Issue date: 09-14-2020 9 / 11

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)
Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance
Not listed.

SARA 311/312 Hazardous No chemical
SARA 313 (TRI reporting) Chemical name CAS number % by
wt.

1,2,4-Trimethyl Benzene	95-63-6	10 - 20
Xylene	1330-20-7	1 - 2.5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6) Safe

Drinking Water Act Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,2,4-Trimethyl Benzene (CAS 95-63-6)

Butane (CAS 106-97-8)

Solvent Naphtha (Petroleum), Light Aromatic (CAS 64742-95-6)

Xylene (CAS 1330-20-7)

US. Massachusetts RTK - Substance List

1,2,4-Trimethyl Benzene (CAS 95-63-6)

Butane (CAS 106-97-8)

Cyclohexanone (CAS 108-94-1)

Propane (CAS 74-98-6)

Xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

1,2,4-Trimethyl Benzene (CAS 95-63-6)

Butane (CAS 106-97-8)

Cyclohexanone (CAS 108-94-1)

Propane (CAS 74-98-6)

Xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

1,2,4-Trimethyl Benzene (CAS 95-63-6)

Butane (CAS 106-97-8)

Cyclohexanone (CAS 108-94-1)

Propane (CAS 74-98-6)

Xylene (CAS 1330-20-7)

US. Rhode Island RTK

1,2,4-Trimethyl Benzene (CAS 95-63-6)

Butane (CAS 106-97-8)

Cyclohexanone (CAS 108-94-1)

Propane (CAS 74-98-6)

Xylene (CAS 1330-20-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

Product name: SO105 SCREEN OPENER

Issue date: 09-14-2020

SDS US

10 / 11

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Cumene (CAS 98-82-8)

Listed: April 6, 2010

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Canada Domestic Substances List (DSL) Yes Canada Non-Domestic Substances List (NDSL) No	
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS) No Japan Inventory of Existing and New Chemical Substances (ENCS) Yes	
Korea	Existing Chemicals List (ECL)	Yes

New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	09 -14-2020
Version #	01
Disclaimer	We cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.
Revision information	This document has undergone significant changes and should be reviewed in its entirety.